

HOOD CHEMICAL
295 ALLIANCE ROAD
MILTON ON L9T 4W8

Tel: 905-876-0707
Fax: 905-876-0695

MATERIAL SAFETY DATA SHEET

EMERGENCY : CANUTEC (613) 996-6666

MSDS: 330-2

PRODUCT IDENTIFICATION AND USE

NAME OF PRODUCT : Plumbing antifreeze

USE OF PRODUCT : protects plumbing systems against freezing

TRANSPORTATION OF DANGEROUS GOODS

SHIPPING NAME :

WHMIS CLASSIFICATION : NOT REGULATED

P.N.I. :

PRIMARY CLASS : NON TOXIC

PACKING GROUP :

SUBSIDIARY CLASS :

COMPONENTS

COMPOSITION	% V/V	CASE #	LD ₅₀ mg/kg Oral/rat	LC ₅₀ ppm 4h	TLV ppm 8h
Propylene glycol	2-27	57-55-6	20 000 - 34000		
Rust inhibitors					

PHYSICAL CHARACTERISTICS

PHYSICAL STATE : Liquid	APPEARANCE : Pink	ODOR : Odorless	ODORTRESHOLD : Not available
VAPOR TENSION : Not available	VAPOR DENSITY (Air = 1): Not available	EVAPORATING RATE : Not available	
BOILING RANGE : 102°C (215°F)	PROTECTION: -51°C	pH : Not available	
DENSITY (20°C) : 1,03	DISTRIBUTION FACTOR WATER/OIL : Not available	SOLUBILITY IN WATER (25°C) : 100%	

REACTIVITY DATA

CHEMICAL STABILITY : Stable under normal storage conditions

INCOMPATIBILITY WITH OTHER PRODUCTS : Avoid oxidizing material.

REACTIVITY CONDITIONS : No hazardous polymerization.

HOOD CHEMICAL
295 ALLIANCE ROAD
MILTON ON L9T 4W8

Tel: 905-876-0707
Fax: 905-876-0695

MATERIAL SAFETY DATA SHEET

EMERGENCY : CANUTEC (613) 996-6666

EXPLOSION AND FIRE RISKS

EXTINGUISHING METHODS : Water fog, alcohol, foam, carbon dioxide,, dry chemical. Do not use a continuous stream of water because this will be propagate fire.

FLASH POINT : >103° C (218°F)

AUTO-IGNITION TEMPS : Not available

FLAMMABILITY: (% per volume)

SUPERIOR LIMIT: 12,5

LOWER LIMIT: 2,6

HAZARDOUS COMBUSTION PRODUCT : When available oxygen id limited, as a fire or when heated to very high temperatures by hot wire or plate, propionaldehyde, carbon monoxide, hazardous compounds such as aldehydes, toxic has and hot identified toxic or irritating compound or the both might be generated.

EXPLOSIBILITY DATA : Not available.

TOXICOLOGICAL PROPERTIES

ABSORPTION WAYS			CONTACT			
SKIN	✓		WITH SKIN	✓	EYES	✓

EFFECTS OF EXPOSURE TO PRODUCT : Product can irritate mucus glands. High doses can provoke headaches, drowsiness, nausea, dizziness and fainting. Inhalation may aggravate cases of emphysema and bronchitis. Repeated contact with skin provokes irritations, dryness of the skin and cracking of the skin.

PREVENTIVE MEASURES

PROTECTIVE EQUIPMENT : Gloves, security glasses and protective apron.

GLOVES : Impervious

RESPIRATORY SYSTEM : Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations, use an approved air-purifying respirator. In misty atmospheres, use an approved mist respirator.

OCULAR INSTRUMENT : Security glasses.

CLOTHING : No precautions other than a clean body covering clothing should be needed..

TECHNICAL CONTROL : At elevated temperatures, special ventilation may be required even of the flash point has not been exceeded. Flammable mists or aerosols can be generated below the flash point of high boiling liquids. Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

PROCEDURE IN CASE OF LEAKS/SPILLS : Spill may contaminate water supplies or pollute public waters. Evacuate and limit access to area. Supply cleanup crew with proper protective equipment. Stop release and prevent flow to sewers or public waters. Notify fire and environmental authorities. Restrict water use for cleanup. This material can create a dangerous slipping hazard on any hard surface. Spread a granular cover (such as sand) or provide open grating on walkways. Impound and recover large land spill. Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Degradation is expected in the atmospheric environment within minutes to hours. Contain and minimize dispersion; collect and contain in suitable disposal containers.

HOOD CHEMICAL
295 ALLIANCE ROAD
MILTON ON L9T 4W8

Tel: 905-876-0707
Fax: 905-876-0695

MATERIAL SAFETY DATA SHEET

EMERGENCY : CANUTEC (613) 996-6666

WASTE DISPOSAL : Contaminated product, soil, water is potentially combustible. Solids may be landfilled at permitted sites in compliance with federal, provincial, local solid waste regulations. Burn concentrated liquid waste. Avoid flameouts and assure emissions comply with regulations. Dilute aqueous wastes may be biodegradable. Avoid overloading and poisoning plant biomass. Effluent must comply with applicable regulations.

STORAGE & HANDLING: This product will absorb water if exposed to air (hygroscopic). Store in tightly closed containers, away from heat, moisture or strong oxidizing agents. Use dry nitrogen to low dew point air for tank padding. Do not heat higher than 10C below flash point unless in a closed system away from air. Do not handle near heat, sparks or open flame.

FIRST AID

SKIN : Wash off in flowing water or shower. Wash clothing before re-use. See a doctor if irritation develops or persists.

EYES : Remove contact lenses. Wash with running water for 29-30 minutes; lift eyelids often. See a doctor if redness, pain or blinking develops or persists.

INHALATION : Remove patient to fresh air if effect occur. Give oxygen of artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential

INGESTION : If a large quantity is swallowed, induce vomiting. Do not give mouth to mouth to an unconscious person. Seek medical attention.

NOTE TO PHYSICIAN : No specific antidote. Supporting care, treatment based on judgement of the physician on response to reactions of the patient.

INFORMATION ON THE M.S.D.S. PREPARATION

PREPARED BY :
LAB PERSONNEL.

TELEPHONE : 905-876-0707

REVISED January, 2014

NOTE :

The information in this detailed M.S.D.S. is available on request, for the customer service. It must not be used for any other purpose and its reproduction and/or publication is forbidden without the consent of HALL CHEM MFG. INC. Even though this information is based on reliable sources, HALL CHEM MFG. INC. cannot guarantee its accuracy and formally excludes all explicit guarantee relative to the exactitude of this information or of the results following its application.